

# ZS-SPGV-40 Globe Valve Weathershield

For Use with Belimo Rotary Actuators



Technical Data	
Gasket	Rubberized PVC
Hardware	Brass inserts and screws
Frame, plate, base	PVC
Housing Material	Grey Rigid Molded PVC
Ambient Temperature Range	-22°F to 122°F [-30°C to +50°C]
Humidity	5 to 95% RH non-condensing
Housing	Designed to Nema 4 standards less holes
Weight	7.3 LB [3.3 kg]

## Application

The ZS-SPGV series weather shields provide moderate protection to globe valve actuators which are mounted outdoors. This product is not designed as a water tight enclosure due to the added holes for mounting. The one piece PVC housing allows for easy mounting of standard rotary style actuators.


## Operation

The ZS-SPGV series weather shields are supplied as a one piece PVC enclosure with a removable cover. Holes can be added in the field to allow for connection of conduit connectors to the housing. There are removable screws to open the cover to mount and access the actuators. Also supplied is a rubberized gasket to ensure a tight seal.

## Suitable Actuators

	Non-Spring	Electronic Fail-Safe
ZS-SPGV-40	GMB(X)	GKB(X)

## Dimensions (Inches [mm])



A	C	D
12.88" [327]	12.88" [327]	4.6" [117]