

ZG-CBNS Junction box



ZG-CBNS

Application

The ZG-CBNS accessory is used when the application requires the wiring terminations to be made at the actuator.

Operation

The ZG-CBNS serves as an electrical junction box. The products that can be used with this accessory are as follows:

AF24 US, AF120 US, AF230 US, AF24-SR US

* Due to the internal volume of this junction box, according to UL requirements, The ZG-CBNS CANNOT be used with the following products:

NF24-S2 US, AF24-S US, AF120-S US, AF230-S US

ZG-CBLS Junction box



ZG-CBLS

Application

The ZG-CBLS accessory is used when the application requires the wiring terminations to be made at the actuator.

Operation

The ZG-CBLS serves as an electrical junction box.

This product can be used with any standard LF product.

M40024 - 05/10 - Subject to change. © Belimo Aircontrols (USA), Inc.

Technical Data	ZG-CBNS / ZG-CBLS
Voltage rating	250 VAC
Electrical connection	maximum 5 line voltage connection
Housing rating	UL94 5VA
Material type	FR/ABS CYCOLAC FR15
Ambient temperature	-22°F to 122°F [-30°C to 50°C]
Storage temperature	-40°F to 176°F [-40°C to 80°C]
Agency listing	UL pending
Quality standards	ISO 9001
Weight	<0.5 lbs