



# Bell & Gossett® ZoneTrol™ II

The next generation of zone controllers from Bell & Gossett brings 21st century technology to residential controls.



ZoneTrol™ II provides DHW priority timer, post purge function and pump exercise into an economical and user-friendly package.

With optional outdoor reset controls, the ZoneTrol II is a natural fit with today's green building strategies. Your modern hydronic systems deserve a modern controller.

Bell & Gossett has been a leader in commercial HVAC pump control systems for nearly 50 years. From our first variable speed pressure boosters to today's Technologic Series controllers, Bell & Gossett is synonymous with advanced design and superb quality.

# ZoneTrol™ II

## Description

ITT's Bell & Gossett ZoneTrol II is a ready-to-install controller for hydronic circulators in residential and light commercial applications. All ZoneTrol II controllers are UL and cUL listed and feature multi-function LEDs that are visible without removing the cover for easy start-up and troubleshooting. All units are compatible with analog and digital 24 VAC thermostats, including "power stealing" designs.

The multi-zone controllers feature an advanced microprocessor design that provides domestic hot water (DHW) priority & timer, pump exercise and a post purge timer **without the need for add-on circuit boards or modules.**

Four and six zone controllers are field expandable for up to 18 pumps and are available with integrated, pre-wired boiler reset or mix reset controllers. Units with reset controllers include all necessary sensors.

Model Number	Part Number	Zones	Combined Load (max.) @ 120 VAC	Dimensions W x L x D Inches (mm)	Weight Lbs (kg)
Z-1	109424	1	5 amps	6.5 x 5 x 3 (165 x 127 x 76)	2.6 (1.18)
Z-2	109425	2	20 amps	6.5 x 5 x 3 (165 x 127 x 76)	3 (1.36)
Z-3	109426	3	20 amps	6.5 x 5 x 3 (165 x 127 x 76)	3.1 (1.4)
Z-4	109427	4	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	7.3 (3.3)
Z-4M	109428	4	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	8.5 (3.9)
Z-4B	109429	4	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	8.5 (3.9)
Z-6	109430	6	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	7.5 (3.4)
Z-6M	109431	6	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	8.7 (3.9)
Z-6B	109432	6	20 amps	13.5 x 8.25 x 3.25 (343 x 210 x 83)	8.7 (3.9)
ZC-11*	109454	Communication cable for connection of multiple controllers			0.1 (0.05)

\* fits 4 and 6 zone controllers only – one required for each slave controller.

### Standard Features (multiple zone controllers only)

- **Priority:** Enables DHW zone to have priority over heating zones for limited period of time. User adjustable settings include OFF (disables priority functionality), 30 minutes and 60 minutes.
- **Post Purge Timer:** Circulator(s) will continue to run for 90 seconds after thermostat opens and allows additional extraction of BTUs from high mass boilers. User adjustable settings are OFF and ON.
- **Exercise:** Runs each circulator for 10 seconds after each 72 hours of inactivity. User adjustable settings are ON and OFF.
- **Expandability:** 4 and 6 zone controllers can easily be connected via an RJ-11 cable to accommodate systems consisting of up to 18 circulators.
- **Five-year Warranty**

### Optional Features (4 and 6 zone controllers only)

- **Boiler Reset:** Incorporates a pre-wired integral boiler reset controller into the ZoneTrol II enclosure. Reset controller cycles the burner to maintain the optimum system supply temperature relative to the outdoor air temperature. Warm weather shutdown functionality can be activated to prevent system operation above a user-selectable outdoor temperature threshold. All necessary sensors are included.
- **Mixing Reset:** For use on hydronic systems incorporating a variable speed injection pump. Incorporates a pre-wired integral mixing reset controller into the ZoneTrol II enclosure. Mixing Reset controller varies the speed of the injection pump to maintain optimum radiant loop temperature relative to the outdoor air temperature. The boiler return temperature is also monitored to ensure that the appropriate minimum water temperature is not violated. Warm weather shutdown functionality can be activated to prevent system operation above a user-selectable outdoor temperature threshold. All necessary sensors are included.



ITT  
8200 N. Austin Avenue  
Morton Grove, Illinois 60053  
Phone: (847) 966-3700  
Fax: (847) 966-9052  
www.bellgossett.com



ITT

Engineered for life