

MATERIAL SPECIFICATIONS

Part Name	Material
Body	Brass
Seat	PTFE
Ball	SS304
Stem O-Ring	NBR
Packing Nut	Brass
Stem	Brass (1/4" - 2") SS304 (2-1/2" - 4")
Lock Nut	Ferrum / Zinc Plated
Lock Washer	Ferrum / Zinc Plated
Packing	PTFE
Handle	Ferrum / Chrome Plated
Cap	Brass

DIMENSIONS

Part#	Size	D	L	H	W	Cv	Wt.(lbs.)
4142	1/4"	0.394	3.46	1.68	1.73	8.23	0.306
4382	3/8"	0.394	3.46	1.68	1.73	8.23	0.302
4122	1/2"	0.524	3.46	1.73	1.89	14.56	0.337
4342	3/4"	0.748	3.46	1.89	2.28	29.76	0.542
0412	1"	0.984	4.29	2.14	2.80	51.55	0.928
41142	1-1/4"	1.240	4.29	2.32	3.15	81.70	1.312
41122	1-1/2"	1.476	5.63	2.66	3.44	115.89	1.865
0422	2"	1.949	5.63	3.01	4.06	200.34	2.994
42122	2-1/2"	2.520	7.76	4.25	5.53	338.43	7.030
0432	3"	2.894	8.19	4.58	6.14	445.44	9.656
0442	4"	3.839	9.25	5.49	7.79	783.88	18.305

Features & Benefits

- For Gas & Non Potable Water Use
- Thread Conform ANSI B1.20.1
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip
- 600 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F

