

### MATERIAL SPECIFICATIONS

Part Name	Material
Body	Brass
Seat	PTFE
Ball	SS304
Stem O-Ring	NBR
Packing Nut	Brass
Stem	Brass (1/2" - 2") SS304 (2-1/2" - 4")
Lock Nut	Ferrum / Zinc Plated
Lock Washer	Ferrum / Zinc Plated
Packing	PTFE
Handle	Ferrum / Chrome Plated
Cap	Brass
Body O-Ring	FKM

### DIMENSIONS

Part#	Size	D	L	H	W	D1	**	Cv	Wt.(lbs.)
4121	1/2"	0.591	3.46	1.81	2.17	0.63	0.504	18.55	0.403
4341	3/4"	0.748	4.29	2.09	2.81	0.878	0.748	29.76	0.670
0411	1"	0.984	4.29	2.25	3.34	1.13	0.909	51.55	1.034
41141	1-1/4"	1.259	5.63	2.52	3.91	1.378	0.972	84.42	1.585
41121	1-1/2"	1.574	5.63	2.74	4.46	1.63	1.091	131.93	2.280
0421	2"	1.949	5.63	3.03	5.45	2.13	1.343	200.35	3.481
42121	2-1/2"	2.520	7.76	4.25	6.42	2.63	1.484	338.43	6.715
0431	3"	2.894	8.19	4.58	7.15	3.13	1.669	445.44	8.655
0441	4"	3.839	9.25	5.49	9.57	4.13	2.232	783.88	17.419

### Features & Benefits

- For Gas & Non Potable Water Use
- Solder-Joint Conform ASME B16.22
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip
- 600 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F

