

3/4" HOSE X 1/2" MIP/SWT • INCLUDES VACUUM BREAKER

Features

- Lead-free design suitable for potable water
- Chrome-plated body offers superior corrosion resistance
- Extended-hub handwheel moves the operator's hands away from the sharp hose bibb threads
- Equipped with an anti-siphon vacuum breaker and internal check valve, to prevent backflow
- Features tapered sill wedge, to ease installation onto a variety of sill types

Specifications & Approvals

Working Pressure, Non-Shock (PSI):
CWP: 125 PSI WSP: Not suitable for steam service

- ANSI / ASME B1.20.7 (MHT outlet)
- Truesdail Labs certified to NSF/ANSI Standard 61/9
- Annex F and Annex G. Meets NSF/ANSI 372
- Certified to A.S.S.E Standard 1019, Type A
- UPC/IAPMO & CSA certified
- Manufactured in an ISO accredited facility



Dimensions

Part#	Nominal Length	L
62061	6"	286
62081	8"	337
62101	10"	388
62121	12"	439

Material Specifications

Part Name	Material
1. Handle Screw	B134-C27000
2. Name Plate	B209-1100
3. Hand Wheel	B86/ABS
4. Stem Gland Screw	B16-C36000
5. Washer	304 Stainless Steel
5-1. Stem Packing	NBR
6. Stop Washer	304 Stainless Steel
7. Body	B584-C857
8-1. Seat	B584-C857
8-2. T Seat	B584-C857
8-3. Tube	B135-C27000
9-1. Stem	B135-C27000
9-2. Piston	B16-C36000
9-3. Spring	304 Stainless Steel
9-4. Disc	B16-C36000
9-5. O-Ring	BUNA-N HS55*
9-6. Diaphragm	Silicon
9-7. Packing Holder	B16-C36000
9-8. Seat Packing	NBR
9-9. Packing Screw	B134-C27000
10. VB Cover	P P
11. VB Body	B16-C36000
12-1. VB Disc	Celcon
12-2. VB Packing	NBR
13. Siding Wedge	LDPE
14. VB O-Ring	BUNA-N HS70*

