

SPECIFICATION SHEET

Push Fittings & Valves

FEATURES & BENEFITS

- Shortens repair time on jobs.
- Lead Free removable brass fittings in sizes 1/2" to 1".
- Certified for potable water and hydronic applications.
- No Tools, No Heat, No Glue, No Flux and No Solder required.
- Connects PEX, CPVC, or COPPER pipe in any combination.
- Quick and easy, removable and reusable installation.
- Made with Lead Free DZR Forged Brass.
- · Ideal for service and repair even on wet lines.
- Pre-lubricated for quick installation.
- · EPDM O-Ring for leak free seals.

SPECIFICATIONS & APPROVALS

- Certified to 200 PSI and 200°F
- Certified by UPC / IAPMO, to meet Lead-Free Potable Water Laws.
- ANSI/NSF-14/G Compliant
- AWWA C800 Compliant
- Meets ASME B1.20.1, ASSE 1061
- Manufactured in an ISO Accredited Facility.

PUSH COUPLINGS



ITEM #	SIZE	А	н
UPSC12	1/2"	52	-
UPSC34	3/4"	60.5	-
UPSC1	1"	70	-
UPSC3412	3/4" x 1/2"	56.3	-
UPSC134	1" x 3/4"	65.6	-

PUSH X FEMALE ADAPTERS




ITEM #	SIZE	А	Н
UPFC12	1/2"	42	-
UPFC34	3/4"	47.3	-
UPFC1	1"	54.3	-
UPFC1234	1/2" x 3/4"	42.5	-
UPFC134	1" x 3/4"	49.8	-

PUSH X MALE ADAPTERS

ſſ	
H	J_H


ITEM #	SIZE	А	н
UPMC12	1/2"	46.5	-
UPMC34	3/4"	48.3	-
UPMC1	1"	54.8	-
UPMC1234	1/2" x 3/4"	46.5	-
UPMC134	1" x 3/4"	53.3	-

FEMALE CENTER TEES




ITEM #	SIZE	Н	L
UPCTF12	1/2"	31	69
UPCTF34	3/4"	37.5	85.2

PUSH TEES




ITEM #	SIZE	Н	
UPET12	1/2"	34.5	69
UPET34	3/4"	42.6	85.2
UPET1	1"	50.8	101.6
UPET121234	1/2" x 1/2" x 3/4"	39.8	77
UPET12121	1/2" x 1/2" x 1"	44.3	73.5
UPET341212	3/4" x 1/2" x 1/2"	38.5	76.8
UPET341234	3/4" x 1/2" x 3/4"	42.8	81.3
UPET343412	3/4" x 3/4" x 1/2"	39.5	85.2
UPET1134	1" x 1" x 3/4"	45.8	94.1

PUSH SLIP COUPLING



ITEM #	SIZE	
UPRC1212	1/2" x 1/2"	105
UPRC3434	3/4" x 3/4"	108.5
UPRT1212	1/2" x 1/2" x 1/2"	105
UPRT3434	3/4" x 3/4" x 3/4"	108.5

PUSH ELBOWS



ITEM #	SIZE		Н
UPE9012	1/2"	35.5	-
UPE9034	3/4"	42.5	-
UPE901	1"	51	-
UPE903412	3/4" x 1/2"	38.5	42.5


*Note: Information subject to change without notice.



SPECIFICATION SHEET

Push Fittings & Valves

PUSH X FEMALE ELBOWS



PUSH X MALE ELBOWS

UPFE12 1/2" UPFE34 3/4"	35.5	32
UPFE34 3/4"		
	42.3	41
UPFE1 1"	50.8	47.5

35.5

42.5

51

36

40

47


SIZE

1/2"

3/4"


1"

PUSH-FIT QUARTER TURN ANGLE STOP



ITEM #	SIZE	Н	L	М
UPASC1214	1/2" x 1/4"	30.9	63.5	36
UPASC1238	1/2" x 3/8"	37.9	63.5	36
UPASP1212	1/2" x 1/2"	40.6	63.5	36

PUSH-FIT QUARTER TURN STRAIGHT STOP




	ITEM #	SIZE	Н	L
<u>h_</u>	UPSSC1214	1/2" x 1/4"	27.5	66
	UPSSC1238	1/2" x 3/8"	27.5	73
Щ	UPSSP1212	1/2" x 1/2"	27.5	75.7

PUSH-FIT ADAPTER W/ EXTENSION



PUSH X FEMALE ELBOW DROP EAR

Т



ITEM #	SIZE	L	Н
UPDEF1212	1/2"	34.5	47

PUSH STOP END

	ITEM #	SIZE	
	UPSE12	1/2"	27.5
	UPSE34	3/4"	31.8
	UPSE1	1"	36.3
1 1			

ITEM #

UPME12

UPME34

UPME1

REMOVAL TOOL

((∠))))
N I	

ITEM #	SIZE		н
UPTR012	1/2"	R8	15.3
UPTR034	3/4"	R11.15	21.3
UPTR001	1"	R14.5	28

*Note: Information subject to change without notice.