



**Functional
Devices, Inc™**

Bulletin B534

• RIBME2401B 393019C

LED ON = RELAY ACTIVATED

CONTACT RATINGS

CONTROL INPUT



TYPE F, G, EM
For use with
Smoke Control System
General Signaling Equip. NM

CONTACTS

CONTROL
INPUT



COIL

Common



5-25 Vac/dc



Common



24 Vac/dc



120 Vac

20A Res. @ 277 Vac
1 HP @ 120 Vac
2 HP @ 277 Vac
20A Ball. @ 120/277 Vac (N/O)
10A Ball. @ 120/277 Vac (N/C)
16A Elect. Ball. @ 277 Vac (N/O)
10A Tung. @ 120 Vac (N/O)
770 VA Pilot @ 120 Vac
1110 VA Pilot @ 277 Vac

.4mA @ 5Vdc
.9mA @ 10Vdc
1mA @ 12Vdc
2mA @ 24Vdc
3mA @ 24Vac

POWER INPUT

47mA @ 30Vdc
83mA @ 24Vac
47mA @ 120Vac

**FOR SUPPLY CONNECTIONS USE # 12 AWG OR
LARGER WIRES RATED AT LEAST 75°C (167°F).**

Functional Devices, Inc.
101 Commerce Drive
Sharpsville, IN 46068
Phone: (800) 888-5538

www.functionaldevices.com

Common



N/O



N/C

