

Honeywell E-Mon

Honeywell E-Mon Class 5000 Smart Meter

ADVANCED KWH/DEMAND METERS WITH COMMUNICATION

SPECIFICATION DATA



Dimensions: 6" H x 6" W x 4 1/4" D

FEATURES

- Advanced 4-line display showing:
 - kWh
 - kW demand (with peak date & time)
 - Power factor per phase
 - Real-time load in kW
 - Amps per Phase
 - Volts per phase
 - On-board set-up option for:
IP address
Meter date/time
ID codes for EZ7, Modbus and BACnet
- 0-2 volt output split-core current sensors allow for enhanced safety and accurate remote mounting of sensors up to 500 feet from meter without power interruption. (Optional solid-core sensors available.)
- Onboard installation diagnostics and verification system.
- Two external meter inputs (water, gas, BTU, etc.) Channels 5 & 6. Pulse count registers not visible on the LCD display may be read via E-Mon Energy, BACnet, or Modbus front end.
- Two pulse outputs
- Phase loss alarm. (N.O. Contact)

- Built-in RS-485 EZ 7 communication capability supports the following connection configurations (or combinations not to exceed 52 devices per channel):
 - Up to 52 Din-Mon D2 & D5, Class 3200, 3400 and 5000 meters and/or IDR interval data recorders
 - Cabling is daisy chain configuration, 3-cond., 22 AWG, up to 4,000 cable ft total per channel.
- Communications:
 - Built-in RS-485 and Ethernet
 - Telephone Modem (optional)
- Protocols:
 - EZ7
 - Modbus RTU
 - Modbus TCP/IP
 - BACnet MS/TP*
 - BACnet IP*
- NOTE: Interval data not available via BACnet.
- Records kWh and kVARh delivered, kWh and kVARh received in first four channels. Data stored in 15-minute intervals for up to 72 days or 5-minute intervals for up to 24 days. Maintains data in a first-in, first-out format.
- Compatible with E-Mon Energy software via EZ7 protocol for automatic meter reading, energy billing and profiling.
- Meter is designed for use on both 3-phase, 3-wire (delta) and 3-phase, 4-wire (wye) circuits. Optional single-phase, 3-wire configuration available.
- Outdoor NEMA 4X polycarbonate enclosure (standard) with padlocking hasp & mounting flanges for indoor/outdoor installation (stand alone) with one 1-1/16" (3/4") KO on bottom of enclosure.
- Optional industrial grade JIC steel enclosure with padlocking hasp and mounting flanges for indoor installation. Knockouts: 1-1/16" (3/4" cond.) bottom, 7/8" (1/2" cond.) top
- UL/CUL listed. Meets or exceeds ANSI C12.20 national accuracy standards. (+/- 0.2% from 1% to 100% of rated load)
- CE Mark approved.
- Meter meets or exceeds MID accuracy standards.



38-00068-01

- BACnet protocol is BTL certified. LonWorks protocol is LonMark certified.**
- MV-90 compatible (with EZ7 only.)**

MODEL NUMBERS

Table 1. 120/208-240V, 127/220V, 3-Phase

Model	Amperage
E50-208100-R01KIT	100 amp
E50-208200-R01KIT	200 amp
E50-208400-R01KIT	400 amp
E50-208800-R01KIT	800 amp
E50-2081600R01KIT	1600 amp
E50-2083200R01KIT	3200 amp

Table 2. 220/380V, 230/400V, 240/415V, 3-Phase.

Model	Amperage
E50-400100-R01KIT	100 amp
E50-400200-R01KIT	200 amp
E50-400400-R01KIT	400 amp
E50-400800-R01KIT	800 amp
E50-4001600R01KIT	1600 amp
E50-4003200R01KIT	3200 amp

Table 3. 277/480V, 3-Phase.

Model	Amperage
E50-480100-R01KIT	100 amp
E50-480200-R01KIT	200 amp
E50-480400-R01KIT	400 amp
E50-480800-R01KIT	800 amp
E50-4801600R01KIT	1600 amp
E50-4803200R01KIT	3200 amp

Table 4. 347/600V, 3-Phase 4 - Wire.

Model	Amperage
E50-600100-R01KIT	100 amp
E50-600200-R01KIT	200 amp
E50-600400-R01KIT	400 amp
E50-600800-R01KIT	800 amp
E50-6001600R01KIT	1600 amp
E50-6003200R01KIT	3200 amp

Enclosure Options

Meters supplied standard in NEMA 4X outdoor enclosures.

Not available in MMU Configuration.

To order a JIC Steel enclosure replace "R" in model number with "J" (E50-208100-J01KIT)

Communication Protocol & Option Packages

The models above represent the O1 protocol package. To specify a different protocol package replace "O1" in model number with the specification below.

RS-485 Port	Ethernet Port	Specify
EZ7	EZ7 Ethernet	O1
Modbus RTU	EZ7 Ethernet	02
BACnet MS/TP	EZ7 Ethernet	03
EZ7	Modbus TCP/IP	04
EZ7	BACnet IP	05
Modbus RTU	Modbus TCP/IP	06

Options

Three-phase meter kits are supplied with (3) split-core current sensors.

To order a single-phase, 3-wire meter kit add "-SP" before "KIT" in the model number. Ex. E50-208100-R01-SPKIT

Single-phase meters will be supplied with (2) split-core current sensors.

CLASS 5000 SMART METER SPECIFICATIONS

- Meter shall be fully electronic with 4 line LCD display showing:
 - kWh
 - kW demand (with peak date and time)
 - Power factor per phase
 - Real-time load in kW
 - Amps per phase
 - Volts per phase
- Meter shall utilize 0-2 volt AC output current sensors to allow paralleling and/or mounting up to 500 feet from meter.
- Sensors shall be of split-core configuration to allow installation without disconnecting cabling, etc. Sensors shall be available from 100 amp to 3200 amp. Sensors shall be optionally available in solid-core configuration (100 & 200 amp.)
- Meter shall provide current sensor installation diagnostics indicator, phase error indicator and phase angle diagnostics on display.
- Meter shall be field programmable for meter date/time, IP address and ID code for communication options.
- Meter shall be enclosed in a NEMA 4X polycarbonate enclosure (standard) with padlocking hasp & mounting flanges for indoor/outdoor installation (stand alone)

- with one 1-1/16" KO on bottom of enclosure. Optional heavy duty JIC steel enclosure available for indoor installation.
- Meter shall be UL/CUL listed to latest applicable standards for safety.
 - Meter shall meet or exceed ANSI C12.20 accuracy standards.
 - Meter shall be CE Mark approved.
 - Meter shall meet or exceed MID accuracy standards.
 - Meter shall provide non-volatile memory to maintain reading during power outages.
 - Meter shall store interval data for kW and kVAR for up to 72 days in first-in first-out format. Interval data not available via BACnet.
 - Meter shall be optionally available in single-phase, 3-wire configuration.
 - Meter shall operate as client device when used with Modbus. Meter works as a server device on BACnet MS/TP.
 - Meter shall provide optional 5th & 6th channel for logging inputs from third-party metering devices (gas, water, BTU, etc.) Both channels provide interval data logging that can be read via Honeywell E-Mon Energy software and Modbus.
 - Meter shall provide two (2) pulse inputs and two (2) pulse outputs.

- Meter shall be capable of daisy-chain connection using RS-485 EZ7 communications in combinations of Din-Mon D2 & D5, Class 3200s, 3400s, 5000s, IDR-8s, IDR-16s not to exceed 52 devices. Cabling shall be through terminal block (3-conductor), 22 AWG, up to 4,000 cable feet total.
- Meter shall be MV-90 compatible (With EZ7 Only)
- Meter shall be available with the following communication protocol & option packages:

RS-485 Port	Ethernet Port	Specify
EZ7	EZ7 Ethernet	01
Modbus RTU	EZ7 Ethernet	02
BACnet MS/TP	EZ7 Ethernet	03
EZ7	Modbus TCP/IP	04
EZ7	BACnet IP	05
Modbus RTU	Modbus TCP/IP	06

- BACnet protocol shall be BTL certified.

Home and Building Technologies

In the U.S.:

Honeywell E-Mon
715 Peachtree Street NE
Atlanta, GA 30308
customer.honeywell.com

® U.S. Registered Trademark
© 2019 Honeywell International Inc.
38-00068-01 M.S. 02-19
Printed in United States

Honeywell E-Mon