


# Lead Free Vacuum Breaker

## Threaded Connection



T-653G



### Features

- 3/4" hose connection
- Tamper-resistant breakaway screw
- Heavy brass construction
- POM internal components
- Wetted surfaces contain less than .25% lead content

### Approvals

- Lead Free Compliant
- ANSI B1.20.7

### Temperature and Pressure Ratings

- 300 WOG - 150 PSI

### Material Specifications

No.	Part	Materials
1	Body	Lead Free Brass
2	Diaphragm*	Buna-N
3	Spring*	Stainless Steel
4	Set Screw	Steel

\*Not shown in drawing

### Dimensions


Part No.	Size	A	B
203-204G	3/4"	1.31	1.25

# Lead Free Chrome-Plated Vacuum Breaker

## Threaded Connection



T-654G



### Features

- 3/4" hose connection
- Tamper-resistant breakaway screw
- Heavy brass construction
- POM internal components
- Wetted surfaces contain less than .25% lead content

### Approvals

- Lead Free Compliant
- ANSI B1.20.7

### Temperature and Pressure Ratings

- 300 WOG - 150 PSI

### Material Specifications

No.	Part	Materials
1	Body	Chrome Plated Lead Free Brass
2	Diaphragm*	Buna-N
3	Spring*	Stainless Steel
4	Set Screw	Steel

\* Not shown in drawing

### Dimensions

Part No.	Size	A	B
203-205G	3/4"	1.31	1.25