

PRESSURE SWITCH 600VAC 12A F SPECIAL

9013FHG13S101J52M1U2X1

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 41.50 USD

Main	
Device short name	FHG
Enclosure type	Standard environment enclosure indoor
Factory modification	Quick connect two-way pressure release valve (for use with polyflow tubing) Maintained manual cut-in lever (AUTO-ON)
Product specific application	Control small electrically driven air compressors
Range of Product	Square D Pumptrol
Complementary	
Adjustable range on rising pressure	70…150 psi (482.63…1034.21 kPa)
Approximate fixed differential	30 psi (206.84 kPa)
Contact code designation	A600
Depth	2.78 in (70.61 mm)
Electrical connection	Slip-on terminal
Fixing Mode	By brackets
Fluid connection type	0.375 inch NPSF internal
Height	2.8 in (71.12 mm)
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	220 psig
Maximum Horse Power Rating	7.5 hp 115 V AC, 1 phase 2 hp 115 V AC, 3 phase 2 hp 230 V AC, 1 phase 3 hp 230 V AC, 3 phase 1 hp 460/575 V AC, 3 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	125 psi (861.84 kPa) off
Net weight	1.13 lb(US) (0.51 kg)
Scale type	Fixed differential
Switch function	DPST

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	3.76 in (95.50 mm)
Environment	
NEMA Degree of Protection	NEMA 1
Product certifications	CSA LR25490 class 3211 06 UL listed file E12158 CCN NKPZ
Ordering and shipping	details
Category	21533 - 9013 FHG (INDIVIDUAL-DISCOUNT CP7I)
Discount Schedule	CP7I
GTIN	00785901049869
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	MX
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

18 months

Warranty