

Rack PDU, Switched, 1U, 20A, 120V, (8)5-20 AP7901B

Call for More Information 800-800-4272



- Includes: Cord retention bracket(s), Horizontal mounting brackets, Installation guide, User manual

Output

Nominal Output Voltage	120V
Maximum Total Current Draw	16
Output Connections	(8) NEMA 5-20R

Input

Nominal Input Voltage	100V, 120V
Input frequency	50/60 Hz
Input Connections	NEMA L5-20P
Cord Length	12.01ft (3.7meters)
Acceptable Input Voltage	100 - 120VAC
Number of Power Cords	1
Load Capacity	1900VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical

Maximum Height	1.73inches (44MM, 4.4CM)
Maximum Width	17.52inches (445MM, 44.5CM)
Maximum Depth	4.25inches (108MM, 10.8CM)
Rack Height	1U
Net Weight	5.0lbs. (2.27KG)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Rack PDU, Switched, 1U, 20A, 120V, (8)5-20 | AP7901B | Downloaded on 03/07/2022 (EST)

Physical	
Shipping weight	7.61lbs. (3.45KG)
Shipping Height	2.76inches (70MM, 7.0CM)
Shipping Width	18.5inches (470MM, 47.0CM)
Shipping Depth	13.5inches (343MM, 34.3CM)
Color	Black

Environmental	
Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA, cUL listed, FCC part 15 class A, ICES-003, Industry Canada, UL 60950, UL listed
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.