



Rack PDU 2G, Metered-by-Outlet, ZeroU, 20A, 208V, (21) C13 & (3) C19

AP8459NA3

Call for More Information 800-800-4272

- APC Metered by Outlet Rack Power Distribution Units (PDUs) provide individual outlet power metering to enable energy optimization and circuit protection. Current metering provides real-time remote monitoring of connected loads. Metered by Outlet Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower total cost of ownership. Metered by Outlet Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra low profile circuit breakers. Users can access and configure Metered by Outlet Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.
- Includes: CAN port terminator, Installation guide, Rack mounting brackets, Safety guide, Serial configuration cable

Output	
Nominal Output Voltage	208V
Maximum Total Current Draw	16
Output Connections	(3) IEC 60320 C19 (21) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	NEMA L6-20P
Cord Length	9.84ft (3meters)
Acceptable Input Voltage	100 - 240VAC
Load Capacity	3300VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical	
Maximum Height	72.01inches (1829MM, 182.9CM)
Maximum Width	2.2inches (56MM, 5.6CM)
Maximum Depth	2.01inches (51MM, 5.1CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Rack PDU 2G, Metered-by-Outlet, ZeroU, 20A, 208V, (21) C13 & (3) C19 | AP8459NA3 | Downloaded on 03/07/2022 (EST)



Physical	
Net Weight	14.9lbs. (6.76KG)
Shipping weight	19.91lbs. (9.03KG)
Shipping Height	80.2inches (2037MM, 203.7CM)
Shipping Width	6.42inches (163MM, 16.3CM)
Shipping Depth	4.61inches (117MM, 11.7CM)
Color	Black
Units per Pallet	48.0

Environmental	
Operating Temperature	23 - 140 °F (-5 - 60 °C)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC part 15 class A, ICES-003, UL listed, VCCI class A, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.