

Safety switch, double throw, non fusible, 200A, 480 VAC/250 VDC, 3 poles, 15 hp, NEMA 1

C82344

Product availability: Stock - Normally stocked in distribution

Price*: 2,813.00 USD

Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	CSA
Enclosure Rating	NEMA 1 galvannealed steel
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Number of Poles	3
Voltage Rating	250 V DC 480 V AC
Wire Size	AWG 6300 kcmil copper or aluminium

Complementary

Maximum Horse Power Rating	15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52	
Tightening torque	275 lbf.in (31.07 N.m) 0.020.20 in ² (13.30127 mm ²) (AWG 6250 kcmil)	
Width	23.88 in (606.55 mm)	
Height	30.88 in (784.35 mm)	
Depth	11.75 in (298.45 mm)	

Ordering and shipping details

Category	00153 - C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901995647
Nbr. of units in pkg.	1
Package weight(Lbs)	64.99 lb(US) (29.48 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	12.20 in (31 cm)
Package 1 width	24.61 in (62.5 cm)
Package 1 Length	32.01 in (81.3 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile