

# APC AV Black 1.5kVA H Type Power Conditioner 120V

H15BLK

Call for More Information 800-800-4272



- Includes: 6 ft gold plated coaxial cable, Rack mounting brackets, RJ11 cable, User manual

Output	
Number of Outlets	12.0
Receptacle Style	NEMA 5-15R

Input	
Nominal Input Voltage	120V
Input frequency	47 - 63 Hz
Input Connections	NEMA 5-15P
Number of Power Cords	1
Input Power	1500 Watts
Maximum Input Current	15.0A

Surge Protection and Filtering	
Surge energy rating	5270Joules
Data Line Protection	Coaxial 2-way splitter with protection, Coaxial video/cable protection, RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines)
Peak Current Common Mode	160kAmps
Peak Current Normal Mode	80 per phasekAmps

Physical	
Maximum Height	3.74inches (95MM, 9.5CM)
Maximum Width	17.01inches (432MM, 43.2CM)
Maximum Depth	9.49inches (241MM, 24.1CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

APC AV Black 1.5kVA H Type Power Conditioner 120V | H15BLK | Downloaded on 03/07/2022 (EST)

Physical	
Rack Height	2U
Net Weight	16.76lbs. (7.6KG)
Shipping weight	22.44lbs. (10.18KG)
Shipping Height	6.61inches (168MM, 16.8CM)
Shipping Width	20.39inches (518MM, 51.8CM)
Shipping Depth	12.68inches (322MM, 32.2CM)
Color	Black
Master Carton Dimensions (Length x Width x Height)	20.76 x 13.14 x 14.15inches (527 x 334 x 359MM)
Master Carton Units	2.0
Master Carton Weight	49.01lbs. (22.23)
Units per Pallet	36.0
SCC Codes	107313040

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA, FCC part 15 class B, FCC part 68, Industry Canada, UL 1012, UL 498
Equipment protection policy	Lifetime : \$750000
Standard warranty	5 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.