

Electronic time delay auxiliary contact block, TeSys K, 1C/O, on delay 1-30s, front, control 110-240 V AC

LA2KT2U

Product availability: Stock - Normally stocked in distribution

facility

Price*: 65.60 USD

Main

| Range | TeSys |
|---|--|
| Product name | TeSys K |
| Product or Component Type | Time delay auxiliary contact block |
| Device short name | LA1 |
| Range compatibility | TeSys K LC1K TeSys K CA2K TeSys K CA3K TeSys K CA4K |
| Mounting Location | Front |
| Pole contact composition | 1 C/O |
| Contacts operation | Time delay |
| Timer type | On delay |
| Time delay range | 130 s |
| [Ue] rated operational voltage | 110240 V AC control circuit 240 V AC signalling circuit |
| Rated operational voltage limits | 0.851.1 Uc |
| [Ith] conventional free air thermal current | 2 A signalling circuit |
| Standards | EN/IEC 60947-5-1 UL 60947-5-1 CSA C22.2 No 60947-5-1 |

Complementary

| · · · · · · · · · · · · · · · · · · | |
|-------------------------------------|---|
| Reset time | 1.5 s during time delay 0.5 s after time delay |
| Insulation resistance | > 10 MOhm |
| Connections - terminals | slip-on terminals |
| Height | 1.06 in (27 mm) |
| Width | 1.50 in (38 mm) |
| Depth | 1.50 in (38 mm) |
| Net weight | 0.09 lb(US) (0.04 kg) |
| | |

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

| Environmental characteristic | Normal environment |
|---------------------------------------|------------------------------|
| IP degree of protection | IP20 conforming to IEC 60529 |
| Protective treatment | TC IEC 60068 |
| Ambient Air Temperature for Operation | 14140 °F (-1060 °C) |

Ordering and shipping details

| Category | 22341 - CONTACTOR,D,K,&F ACCESS |
|-----------------------|---------------------------------|
| Discount Schedule | l12 |
| GTIN | 3389110230086 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.53 oz (43.4 g) |
| Returnability | Yes |
| Country of origin | TN |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|------------------------|
| Package 1 Height | 1.89 in (4.8 cm) |
| Package 1 width | 1.89 in (4.8 cm) |
| Package 1 Length | 1.97 in (5 cm) |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 70 |
| Package 2 Weight | 7.41 lb(US) (3.361 kg) |
| Package 2 Height | 5.91 in (15 cm) |
| Package 2 width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| | |

Offer Sustainability

| REACh Regulation | REACh Declaration |
|----------------------------|--|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| | |