



Multi9 - shunt trip release with OC contact - MX + OF - 12/24 V AC - 12/24 V DC

M9A26948

Product availability: Stock - Normally stocked in distribution facility

Price*: 140.00 USD

Main

Range of product	Multi 9
Product or Component Type	Shunt trip release with OC contact
Device short name	MX + OF
Signal contacts composition	1 C/O
[le] rated operational current	6 A <= 240 V AC
[Uc] control circuit voltage	1224 V AC 50/60 Hz 1224 V DC
9 mm pitches	2

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP GFP Multi 9 C60H-DC C60H-DC
Local signalling	Action indicator
Mounting Mode	Fixed
Mounting Support	DIN rail
Height	3.25 in (82.5 mm)
Width	0.71 in (18 mm)
Depth	2.68 in (68 mm)
Net weight	0.14 lb(US) (0.065 kg)
Connections - terminals	Clamp terminal bottom) - 1 0.00 in² (2.5 mm²) AWG 14) - rigid Clamp terminal bottom) - 2 0.00 in² (1.5 mm²) AWG 16) - rigid
Wire stripping length	0.35 in (9 mm) bottom
Tightening torque	8.85 lbf.in (1 N.m) bottom

Environment

Standards	EN/IEC 60947-1
Product certifications	CCC PCT UL CSA UR

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Life Is On Schneider

Pollution degree	3
Ambient Air Temperature for Operation	-13122 °F (-2550 °C)
Ambient Air Temperature for Storage	-40185 °F (-4085 °C)

Ordering and shipping details

00948 - M9 GEN 2 CB UL1077 / IEC
DE2
3606480639098
1
2.65 oz (75 g)
Yes
BE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.18 in (3 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	3.70 in (9.4 cm)
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	23.42 oz (664 g)
Package 2 Height	3.94 in (10 cm)
Package 2 width	3.54 in (9 cm)
Package 2 Length	10.63 in (27 cm)
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Weight	14.26 lb(US) (6.469 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	11.81 in (30 cm)
Package 3 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.