



Overview

Presentation	Network appliances enabling remote and local access control for your NetShelter SX enclosures.
Lead time	Usually in Stock

General

Provided equipment	Cable ties Door sensor Installation guide Lock handles Proximity card Proximity reader Rack mounting brackets User manual
Connections supported	Alarm beacon 1 Modbus Output (RS-485) 1 Relay output 1
Universal sensor supported	Door contact Dry contact Humidity Smoke Fluid spot leak Temperature Vibration
Product compatibility	Rack sensor pod 150
Number of universal sensor ports	6
Number of sensor pods supported	6
Measurement range	15...50 °C +/- 1 °C 32...122 °F +/- 1.8 °F

Physical

Depth	5.9 cm
Height	4.4 cm
Net weight	1.27 kg
Number of rack unit	1U

Width	43.2 cm
-------	---------

Environmental

Ambient air temperature for operation	0...45 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.00...15240.00 m

Communications & Management

Communication port protocol	A-Link SNMP
-----------------------------	----------------

Packing Units

Package 1 Weight	2.45 kg
Package 1 Height	19.37 cm
Package 1 width	90.4 cm
Package 1 Length	52.9 cm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---
