

Technical Specifications

APC Performance SurgeArrest 11 Outlets with 2 USB charging ports (5V, 2.4A in total), 120V | P11U2 | Downloaded on 03/07/2022 (EST)



APC Performance SurgeArrest 11 Outlets with 2 USB charging ports (5V, 2.4A in total), 120V P11U2

Call for More Information 800-800-4272

- Includes: User manual

Output

Number of Outlets	11.0
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	8.01ft (2.4meters)
Number of Power Cords	1

Surge Protection and Filtering

Surge energy rating	2880Joules
ts_nm_surge_response	1ns
Peak Current Common Mode	20kAmps
Peak Current Normal Mode	60kAmps

Physical

Maximum Height	1.57inches (40MM, 4.0CM)
Maximum Width	4.69inches (119MM, 11.9CM)
Maximum Depth	11.89inches (302MM, 30.2CM)
Net Weight	2.23lbs. (1.01KG)
Shipping weight	2.47lbs. (1.12KG)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Height	2.36inches (60MM, 6.0CM)
Shipping Width	7.48inches (190MM, 19.0CM)
Shipping Depth	13.39inches (340MM, 34.0CM)
Color	Black
Master Carton Dimensions (Length x Width x Height)	14.75 x 14 x 15.75inches (375 x 356 x 400MM)
Master Carton Units	12.0
Master Carton Weight	31.2lbs. (14.15)
Units per Pallet	216.0
SCC Codes	10731304322990

Environmental	
Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	MET Canada, MET USA
Equipment protection policy	Lifetime : \$250000
Standard warranty	Limited Lifetime

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.