

Technical Specifications

APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V | P11VNT3 | Downloaded on 03/07/2022 (EST)



APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V

P11VNT3

\$49.99*

Call for More Information 800-800-4272

- Includes: 6 ft network cable, Coaxial cable, Cord management straps, Telephone cable, User manual

Output	
Number of Outlets	11.0
Receptacle Style	NEMA 5-15R

Input	
Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-15P
Cord Length	8.01ft (2.4meters)
Number of Power Cords	1

Surge Protection and Filtering	
Surge energy rating	3020Joules
Data Line Protection	Coaxial cable for CATV/SATV/modem/audio-video, RJ11 analog phone line for phone/fax/modem/DSL, RJ45 network line - 10/100 base-T Ethernet

Physical	
Maximum Height	1.57inches (40MM, 4.0CM)
Maximum Width	4.69inches (119MM, 11.9CM)
Maximum Depth	11.89inches (302MM, 30.2CM)
Net Weight	2.34lbs. (1.06KG)
Shipping weight	2.98lbs. (1.35KG)
Shipping Height	2.36inches (60MM, 6.0CM)

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Performance SurgeArrest 11 Outlet with Phone (Splitter), Coax and Ethernet Protection, 120V | P11VNT3 | Downloaded on 03/07/2022 (EST)

Physical	
Shipping Width	7.56inches (192MM, 19.2CM)
Shipping Depth	13.58inches (345MM, 34.5CM)
Color	Black
Master Carton Dimensions (Length x Width x Height)	15 x 8 x 15inches (381 x 203 x 381MM)
Master Carton Units	6.0
Master Carton Weight	19.58lbs. (8.88)
SCC Codes	10731304249020

Environmental	
Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA, NOM, UL 1363, UL 1449
Equipment protection policy	Lifetime : \$100000
Standard warranty	Limited Lifetime

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

*Prices are indicative

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.