

Technical Specifications

APC SERVICE BYPASS PDU, 120V 20AMP W/ (6) NEMA 5-15R AND (2) 5-20R | SBP2200RM | Downloaded on 03/07/2022 (EST)



APC SERVICE BYPASS PDU, 120V 20AMP W/ (6) NEMA 5-15R AND (2) 5-20R SBP2200RM

Call for More Information 800-800-4272

- Includes: Rack mounting brackets, User manual

Output	
Nominal Output Voltage	120V
Efficiency at Full Load	99 % %
Always on Outlets	10
Overload Protection	Yes
Cord Length	4ft (1.2meters)
Maximum Total Current Draw	20
Output Connections	(6) NEMA 5-15R (2) NEMA 5-20R

Input	
Nominal Input Voltage	120V
Input frequency	50/60 Hz
Input Connections	NEMA 5-20P
Cord Length	8.01ft (2.4meters)
Acceptable Input Voltage	100 - 125VAC
Number of Power Cords	1
Efficiency at Full Load	99 % %
Load Power Factor Range	0 to 1
Load Capacity	2200VA
Maximum Input Current	20A
Maximum Line Current	20A

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Maximum Height	3.5inches (89MM, 8.9CM)
Maximum Width	17.01inches (432MM, 43.2CM)
Maximum Depth	2.99inches (76MM, 7.6CM)
Rack Height	2U
Net Weight	6.5lbs. (2.95KG)
Shipping weight	8.38lbs. (3.8KG)
Shipping Height	5.94inches (151MM, 15.1CM)
Shipping Width	18.23inches (463MM, 46.3CM)
Shipping Depth	11.61inches (295MM, 29.5CM)
Color	Black
Units per Pallet	56.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 15000ft (0 - 4572meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	TÜV
Standard warranty	2 years repair or replace

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.