

Technical Specifications

APC Service Bypass Panel- 100-120V; 30A; BBM; L5-30P input; (2) 5-20R (6) 5-15R output | SBP3000RM2U | Downloaded on 03/07/2022 (EST)



APC Service Bypass Panel- 100-120V; 30A; BBM; L5-30P input; (2) 5-20R (6) 5-15R output SBP3000RM2U



Call for More Information 800-800-4272

- Includes: Installation guide, Rack mounting brackets, User manual

Output	
Nominal Output Voltage	100V, 120V
Efficiency at Full Load	99 % %
Other Output Voltages	110 V
Overload Protection	Yes
Cord Length	10.01ft (3.1meters)
Maximum Total Current Draw	30
Output Connections	(2) NEMA 5-20R (6) NEMA 5-15R

Input	
Nominal Input Voltage	100V, 120V
Input frequency	50/60 Hz
Input Connections	NEMA L5-30P
Cord Length	10.01ft (3.1meters)
Number of Power Cords	1
Efficiency at Full Load	99 % %
Load Power Factor Range	0 to 1
Load Capacity	3000VA
Maximum Input Current	24A
Maximum Line Current	24A

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

APC Service Bypass Panel- 100-120V; 30A; BBM; L5-30P input; (2) 5-20R (6) 5-15R output | SBP3000RM2U | Downloaded on 03/07/2022 (EST)

Physical	
Maximum Height	3.5inches (89MM, 8.9CM)
Maximum Width	17.01inches (432MM, 43.2CM)
Maximum Depth	25.51inches (648MM, 64.8CM)
Rack Height	2U
Net Weight	30.07lbs. (13.64KG)
Shipping weight	54.15lbs. (24.56KG)
Shipping Height	7.99inches (203MM, 20.3CM)
Shipping Width	24.02inches (610MM, 61.0CM)
Shipping Depth	39.02inches (991MM, 99.1CM)
Color	Black

Environmental	
Operating Temperature	-4 - 122 °F (-20 - 50 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 15000ft (0 - 4572meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Approvals	CSA, EN 60950, GOST, IEC 60950, UL 1778
Standard warranty	2 years (parts only)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.