



### Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

### General

Provided equipment	Installation guide Rack mounting hardware Rack mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable Cat 5 Ethernet cable
Product web sub-family	Extended run
Performance multiplier	1
Number of tare power	5.6 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S
Value multiplier	1

### Physical

Cable length	2.44 m
Number of rack unit	2U
Colour	Black
Depth	49 cm
Height	8.9 cm
Mounting location	Front
Mounting preference	Lower
Net weight	24.82 kg
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes
Width	43.2 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

## Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Input voltage limits	75...154 V adjustable 82...143 V
Maximum input current	12 A
Switching current capacity	20 A
Max short time withstand current	1000 kA
Number of cables	1
Input voltage	120 V

## Output

Rated power in W	1350 W
Harmonic distortion	Less than 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 NEMA 5-15R
Curve equation	Efficiency
Curve fixed loss	0.0032
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.0095
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Full load runtime	00:05:00
Graph display	1
Half load runtime	00:15:00
Output voltage	120 V
Maximum configurable power in VA	1440 VA
Rated power in VA	1440 VA

## Conformance

Product certifications	CUL listed
Standards	UL 1778
Equipment protection policy	Lifetime : \$150000

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft

Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	40 dBA
Heat dissipation	133 Btu/h
Show note OP temperature	No

### Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0
Battery voltage	48 V
Battery curve	D
Battery charger power	103 W rated
Battery power in VAH	288 VAh runtime
Battery life	3...5 year(s)
Battery option	SMX48RMBP2U 5 3303 VAh SMX48RMBP2U 4 2700 VAh SMX48RMBP2U 3 2100 VAh SMX48RMBP2U 2 1495 VAh SMX48RMBP2U 1 888 VAh
Extended runtime	0

### Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

### Surge Protection and Filtering

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

### Packing Units

Package 1 Weight	30 kg
Package 1 Height	24.6 cm
Package 1 width	58.9 cm
Package 1 Length	62 cm
Number of Units in Package 3	8

### Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---