



Main

| | |
|---------------------------|---------------|
| Range of product | Harmony 9001K |
| Product or component type | Pilot light |
| Device short name | K |

Complementary

| | |
|-----------------------------|---|
| Bezel material | Chromium plated metal |
| Mounting diameter | 30 mm |
| Lens type | Fresnel (plastic) |
| Cap/Operator or lens colour | Red |
| Light source | Incandescent |
| Bulb base | BA 9s |
| Light block supply | Full voltage 28 V Direct 24 V |
| Connections - terminals | Screw clamp terminals (1 x 0.22...2 x 1.5 mm ²) conforming to IEC 60947-1 |
| Shape of screw head | Round head |
| Operating position | Any position |
| [Us] rated supply voltage | 24...28 V AC/DC |
| Operating mode | Normal |
| Device presentation | Complete product |

Environment

| | |
|---------------------------|---|
| Product certifications | UL listed file E42259 CCN NKCR CSA LR25490 class 3211 03 CE |
| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13 |

Offer Sustainability

| | |
|------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
|------------------------|---|

REACH

Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold
