

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 350.00 USD



### Main

Range of product	Harmony 9001KY
Product or component type	Control station
Device short name	9001SK
Provided equipment	Label plate with START-STOP marking
Contact block name	KA1 KA3

### Complementary

Enclosure/Cubicle description	Wall-mounted enclosure with 2 cut-outs
Enclosure material	Polymeric
Type of installation	Indoor/outdoor
Control station composition	2 push-buttons with 1 NO + 2 NC contacts
Connector type	Screw clamp connector
[Ue] rated operational voltage	600 V
[Ie] rated operational current AC	10 A

### Environment

NEMA degree of protection	NEMA 1 NEMA 13 NEMA 3 NEMA 4
Environmental characteristic	Resistant against immersion in water Dust and oil resistant
Product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

## Ordering and shipping details

Category	21429 - 9001 SK,SKY
Discount Schedule	CS1
GTIN	00785901154181
Nbr. of units in pkg.	1
Package weight(Lbs)	2.02
Returnability	N
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1002 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Nickel compounds, which is known to the State of California to cause cancer, and
----- Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
----- More information	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------