Product data sheet Characteristics

9012GFW1G18

pressure switch 9012G - fixed scale - 1 threshold - 20 to 1000 PSIG psig

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 659.00 USD



Main

IVIAIII		
Range of product	9012G	
Pressure sensor type	Electromechanical pressure switch	
Pressure sensor name	9012G	-
Pressure sensor size	1000 psi	: <u>:</u> :: ::
Maximum pressure	1000 psi	<u> </u>
Contacts type and composition	NC-NO, 2 SPDT-DB, Form Z, snap action, silver nickel contacts	
Controlled fluid	Air Non-corrosive liquids Non-corrosive gas Hydraulic oil (-15250 °F)	otomininininininininininininininininininin
Fluid connection type	0.25 inch 18 NPTF conforming to UL 508	
Pressure switch type of operation	Detection of 1 single threshold	
Scale type	Fixed	
Local display	Without	

Complementary

201000 psi	
59 psi +/- 2.5 % full scale	
0.5 inch NPT conduit entrance	
4 screw terminals	
Screw-clamp terminals, AWG 22AWG 12	
Control circuit	
1 neon (red) AC/DC at 120 V (voltage limits:105125 V	
6 A (Ue = 120 V AC) 0.22 A (Ue = 125 V DC)	is doesn't
Internal	
Die cast aluminium alloy 380	<u>a</u> . 20
	59 psi +/- 2.5 % full scale 0.5 inch NPT conduit entrance 4 screw terminals Screw-clamp terminals, AWG 22AWG 12 Control circuit 1 neon (red) AC/DC at 120 V (voltage limits:105125 V 6 A (Ue = 120 V AC) 0.22 A (Ue = 125 V DC) Internal

Pressure actuator	Piston	
Height	6.24 in	
Depth	4.56 in	
Width	5.05 in	
Operating position	Any position	
Materials in contact with fluid	Teflon Viton fluorocarbon 440 stainless steel 303 stainless steel	
Short-circuit protection	10 A by gL (cartridge) overload and short-circuit protection	
Operating rate	<= 120 cyc/mn	
Mechanical durability	3000000 cycles	
Repeat accuracy	4 %	
Product weight	3 lb(US)	

Environment

Vibration resistance	2 gn conforming to IEC 68-2-6 (f = 40150 Hz)
Shock resistance	50 gn conforming to IEC 58-2-27
Standards	CE UL 508 CSA C22.2 No 14
Product certifications	CE CSA LR25490 class 3211 03 UL listed file E12158 CCN NKPZ
NEMA degree of protection	NEMA 4/4X/13 conforming to UL 50
Ambient air temperature for operation	-10185 °F

Ordering and shipping details

Category	21522 - 9012 G INDUSTRIAL PRESSURE SWITCHES
Discount Schedule	CP7G
GTIN	00785901024927
Nbr. of units in pkg.	1
Package weight(Lbs)	3
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Available	
California proposition 65	WARNING: This product can expose you to chemicals including:	
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	
More information	For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty period	18 months	