



Main

| | |
|---------------------------------------|---|
| Range of product | Modicon X80 |
| Accessory / separate part type | Preformed cordset |
| Accessory / separate part designation | Preformed cordset with one end with flying leads |
| Accessory / separate part destination | For I/O module with 40-way connectors |
| Number of cables | 2 |
| Electrical connection | 1 connector 40 ways 2 ends with color-coded flying leads conforming to DIN 47100 |
| Cable length | 5 m |

Complementary

| | |
|-----------------------|--|
| Total number of wires | 40 |
| Wire section | 0.324 mm ² |
| AWG gauge | AWG 22 |
| Relative impedance | 10 MOhm for <= 50 V 100 MOhm for 50...250 V |
| Net weight | 1.49 kg |

Environment

| | |
|-----------|--|
| Standards | CSA C22.2 No 142 EN/IEC 61131-2 UL 508 |
|-----------|--|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |

| | |
|----------------------------|---|
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|