



## Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of ventilation filter	Standard
Air flow	Free flow rate with standard filter: 80 m <sup>3</sup> /h at 50 Hz
[Us] rated supply voltage	10...27.6 V
Input voltage	24 V DC 50/60 Hz

## Complementary

Power range	7.6 W 50 Hz
[In] rated current	0.3 A 50 Hz
Noise level	46...49 dB
Bearing type	Ball
Height	External: 170 mm
Width	External: 150 mm
Depth	External: 62 mm
Cut-out dimensions	125 x 125 mm
Product weight	0.48 kg
Material	Injected thermoplastic (ASA PC) for outlet grille
Colour	Outlet grille: grey RAL 7035
Ambient air temperature for operation	-10...70 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	50 Pa flow rate 0 m <sup>3</sup> /h
Connections - terminals	Faston connector
IP degree of protection	IP54
Device composition	1 outlet grille front 1 axial motor 2 protective grille on the front and rear surfaces 1 filter front of axial motor 1 cut-out template 1 power cord
Condition of use	Outside temperature must be 5 °C lower than inside temperature Surrounding environment must be relatively clean

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overfrequent filter replacement should be avoided  
Filter must be cleaned and replaced regularly  
Flow rates depends on the work point, see ProClima software

---

### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

### Contractual warranty

Warranty period	18 months
-----------------	-----------

---