

### Main


|                                    |   |
|------------------------------------|---|
| Range                              | Spacial   |
| Accessory / separate part category | Mounting accessory  |
| Product or component type          | Mounting plate  |
| Device application                 | Multi-purpose   |
| Mounting location                  | Step slide<br>Direct fixing on backstuds                  |
| Mounting plate description         | Plain   |
| Range compatibility                | Spacial CRN<br>Spacial S3D<br>Spacial S3X<br>Thalassa PLM |
| Quantity per set                   | Set of 1  |
| Material                           | Fibreglass reinforced polyester                           |
| Colour                             | Grey RAL 7035   |

### Complementary

|                            |   |
|----------------------------|---|
| Fixing mode                | Screwed on backstuds - screw type M8<br>By fixing element |
| Permanent permissible load | 875 kg  |
| Height                     | 665 mm  |
| Width                      | 450 mm  |
| Thickness                  | 4 mm  |
| Product weight             | 2.1 kg  |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Green Premium product   |
| RoHS (date code: YYWW)   | Compliant - since 0940 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |

|                                  |  |
|----------------------------------|--|
| REACH                            | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold               |
| Product environmental profile    | Available<br> Product environmental |
| Product end of life instructions | Need no specific recycling operations  |
| <b>Contractual warranty</b>      |  |
| Warranty period                  | 18 months  |