NSYTRAPLOT

Marking Plotter for unprinted NSYTRA marking cards and ZBY marking elements



Main	
Range	Linergy
Product name	TR
Product or component type	Flatbed plotter
Device short name	TRA
Accessory / separate part category	Marking accessory

Complementary

Product compatibility	TRA type marking card
	HP plotter pen
	ZBY type legend
[Ue] rated operational voltage	Internal supply: 24 V
	External supply: 100240 V
[le] rated operational current	Internal supply: 1.25 A
	External supply: 0.7 A
Material	Aluminium
Provided equipment	Installation guide
	Documentation
	USB cable
	Power supply
Integrated connection type	USB port
Label dimensions	220 x 305 mm
Passing speed of object	40 mm/s
Buffer size	16 MB
Motor type	2-phase stepper motor
Repeat accuracy	+/- 0.05 mm
Height	125 mm
Width	440 mm
Length	440 mm
Product weight	6 kg
Colour	Grey

Environment

Standards	EN 55022 Class B	
	EN 60950-1	
	EN 61000-4-11	
	EN 61000-4-2	
	EN 61000-4-3	
	EN 61000-4-4	
	EN 61000-4-5	
	EN 61000-4-6	
Ambient air temperature for operation	1035 °C	
Ambient air temperature for storage	-1050 °C	
Relative humidity	1090 % , in storage	
	3575 % , in operation	