



Main

Product or component type	Additional I/O module
Range compatibility	Altivar Process ATV600 Altivar Machine ATV340 Altivar Process ATV900 Easy Altivar 610
Input/Output type	2 analog input configurable voltage, current or probe 6 discrete input 2 discrete output
Analogue input number	2
Analogue input type	AI1, AI2 configurable current: 0...20 mA/4...20 mA, sampling time: 0...1 ms, resolution: 14 bits AI1, AI2 configurable voltage: - 10...10 V DC, 24 V max, impedance: 20 kOhm, sampling time: 0...1 ms, resolution: 14 bits AI1, AI2 configurable PTC, Pt 100, Pt 1000, sampling time: 0...1 ms, resolution: 14 bits
Discrete output number	2
Discrete output type	(DQ11, DQ12) assignable logic, sampling time: 1 ms
Discrete output logic	(DQ11, DQ12) negative (DQ11, DQ12) positive
Discrete input number	6
Discrete input type	(DI11...DI16) programmable, impedance: 250 Ohm, sampling time: 1 ms
Discrete input logic	Negative (DI11...DI16) Positive (DI11...DI16)
Discrete input current	2.5 mA

Complementary

Discrete output voltage	24 V DC (voltage limits: <= 30 V) assignable logic
Maximum output current	100 mA, assignable logic
Discrete input voltage	24 V DC (voltage limits: <= 30 V) for programmable
Electrical connection	Removable spring terminal block, 1.5 mm ² / AWG 16
Protection type	Reverse polarity protection: digital input Short-circuit protection: output
Net weight	0.5 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
-------------------	---

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
