



Price* : 360.00 USD



Main

| | |
|---------------------------|------------------|
| Range of product | Harmony XVS |
| Product or component type | Multisound siren |
| Device short name | XVS |

Complementary

| | |
|--|---|
| Color | White |
| Material | PC (polycarbonate) (back cover) ASA (Acrylonitrile Styrene Acrylate) (front) ASA (Acrylonitrile Styrene Acrylate) (back) |
| Product weight | 2.2 lb(US) (1 kg) |
| Marking | CE |
| Mounting support | Bracket |
| Fixing mode | 3 holes Ø 9 mm |
| [Uimp] rated impulse withstand voltage | 0.8 kV |
| Current consumption | 250 mA at 12 V 350 mA at 24 V |
| Electrical connection | Cable: 0.26...0.33 in (6.5...8.5 mm), 0 in ² (0.33 mm ²) / AWG 22 (signalling circuit) Cable: 0.26...0.33 in (6.5...8.5 mm), 0 in ² (0.52 mm ²) / AWG 20 (power circuit) |
| Width | 5.51 in (140 mm) |
| Height | 4.49 in (114 mm) |
| Depth | 8.78 in (223 mm) |

Environment

| | |
|------------------------|--|
| Signalling type | 43 tones siren |
| Standards | EN 55014-2 EN 55022 EN 61000-6-2 EN 61000-6-3 |
| Product certifications | UL |

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient air temperature for storage | -31...158 °F (-35...70 °C) |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C) |
| Overvoltage category | Class II conforming to EN/IEC 61140 |
| IP degree of protection | IP53 conforming to EN/IEC 60529 |
| [Us] rated supply voltage | 12 V DC 24 V DC |
| Noise level | 0...105 dB (continuous or intermittent tone)at 1 m |

Ordering and shipping details

| | |
|-----------------------|--------------------------|
| Category | 22617 - XVC TOWER LIGHTS |
| Discount Schedule | XV |
| GTIN | 00785901811237 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.02 |
| Returnability | Y |
| Country of origin | ID |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1611 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |
| California proposition 65 | WARNING: This product can expose you to chemicals including: |
| ----- Substance 1 | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| ----- More information | For more information go to www.p65warnings.ca.gov |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|