Product data sheet Characteristics

XZCP1764L5

pre-wired connectors XZ - straight female - 7/8"16 UN - 5 pins - cable PUR 5m





Main

Accessory / separate part category	Cabling accessory	_;
Accessory / separate part type	Pre-wired connectors	_
Series name	General purpose	- 3

Complementary

Electrical connection	7/8"16 UN, 5 pins (included earth pin) straight female connector	<u>.</u> (
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.9 mm	.
Cable composition	5 x 0.34 mm²	7
Wire insulation material	PUR	-
[Ue] rated operational voltage	250 V AC	•
[In] rated current	4 A	<u>.</u> 7
Contact resistance	5000 μOhm	Ş
Insulating resistance	1 GΩ	· · · · · · · · · · · · · · · · · · ·
Product weight	0.46 kg	
	· · · · · · · · · · · · · · · · · · ·	

Environment

IP degree of protection	IP67	
Product certifications	CULus	
Ambient air temperature for operation	-3590 °C (static) -590 °C (flexing)	
Ambient air temperature for storage	-35100 °C	


Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Available
	☑ End of life manual

Contractual warranty

Warranty period	18 months

Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCP1764L5

Connections and Schemes

Connector



BU: Blue BN: Brown BK: Black

Y/G: Yellow / Green BK/WH: Black / White