



Overview

Model Name	APC Smart-UPS SRT 2200VA RM 120V Network Card
Includes	CD with software , Documentation CD , Installation guide , Network Management Card , Rack Mounting brackets , Rack Mounting support rails , Rack mounting hardware , USB cable , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla , Antigua And Barbuda , Argentina , Aruba , Bahamas , Barbados , Belize , Bermuda , Bolivia , Canada , Cayman Islands , Chile , Colombia , Costa Rica , Cuba , Dominica , Dominican Republic , Ecuador , El Salvador , Falkland Islands (Malvinas) , Grenada , Guatemala , Guyana , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Paraguay , Peru , Puerto Rico , SAINT KITTS AND NEVIS , SAINT LUCIA , SAINT VINCENT AND THE GRENADINES , Trinidad And Tobago , United States , Uruguay , Venezuela , VIRGIN ISLANDS (UNITED STATES)

Output

Output Power Capacity	1800 Watts / 2200 VA
Max Configurable Power (Watts)	1800 Watts / 2200 VA
Nominal Output Voltage	120V
Output Voltage Distortion	Less than 2%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Crest Factor	3 : 1
Crest Factor	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(1) NEMA L5-20R (Battery Backup) , (6) NEMA 5-20R (Battery Backup)
Bypass	Built-in Bypass

Input

Nominal Input Voltage	120V
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	NEMA 5-20P
Cord Length	1.83 meters
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	3 hour(s)
Replacement Battery	APCRBC141
RBC Quantity	1

Communications & Management

Interface Port(s)	RJ-45 10/100 Base-T , RJ-45 Serial , Smart-Slot , USB
Available SmartSlot™ Interface Quantity	0
Pre-Installed SmartSlot™ Cards	AP9631
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	340 Joules
Filtering	--

Physical

Maximum Height	85.0 mm
Maximum Width	432.0 mm
Maximum Depth	584.0 mm
Rack Height	2 U
Net Weight	25.0 kg
Shipping Weight	34.03 kg
Shipping Height	246.0 mm
Shipping Width	599.0 mm
Shipping Depth	810.0 mm
Master Carton Units	0.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	12.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 50 °C
Storage Relative Humidity	0 - 95% non-condensing %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	55.000 dB
Online Thermal Dissipation	535.000 BTU/hr
Protection Class	IP 20

Conformance

Approvals	CSA C22.2 No.107.3-05 , ENERGY STAR V1.0 (USA) , FCC Part 15 Class A , OSHPD , UL 1778
-----------	--

Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery
-------------------	---

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
