



APC Smart-UPS RT Tower Isolation/Step-Down Transformer

SURT003

Call for More Information 800-800-4272

- Includes: Installation guide, User manual

Output	
Nominal Output Voltage	120V, 208V
Other Output Voltages	240 V
Overload Protection	Yes
Maximum Total Current Draw	30
Output Connections	(2) NEMA L6-20R (1) NEMA L6-30R (1) NEMA L14-30R (8) NEMA 5-20R

Input	
Nominal Input Voltage	208V, 240V
Input frequency	50/60 Hz
Input Connections	NEMA L6-30P
Cord Length	2.99ft (0.9meters)
Acceptable Input Voltage	180 - 264VAC
Number of Power Cords	1
Load Capacity	4800VA
Maximum Input Current	30A

Physical	
Maximum Height	17.01inches (432MM, 43.2CM)
Maximum Width	5.12inches (130MM, 13.0CM)
Maximum Depth	25.98inches (660MM, 66.0CM)

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Rack Height	3U
Net Weight	125.27lbs. (56.82KG)
Shipping weight	140.3lbs. (63.64KG)
Shipping Height	13.66inches (347MM, 34.7CM)
Shipping Width	23.74inches (603MM, 60.3CM)
Shipping Depth	38.58inches (980MM, 98.0CM)
Color	Black
Units per Pallet	6.0

Environmental	
Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.